

RML Example 55 : Condpagebreak



RML (Report Markup Language) is ReportLab's own language for specifying the appearance of a printed page, which is converted into PDF by the utility rml2pdf.

These RML samples showcase techniques and features for generating various types of output and are distributed within our commercial package as test cases. Each should be self explanatory and stand alone.

KeepWithNext

The `keepWithNext` attribute for the `paraStyle` tag tells the paragraph, whether it should always be kept together with the next paragraph or not. This can be useful for keeping headings together with the following paragraph. The default value is 0.

The code looks as follows:

```
<paraStyle name="keepApart" keepWithNext=1>
<paraStyle name="keepTogether" keepWithNext=0>
```

An example with `keepWithNext="0"`. There is a spacer underneath.

This is paragraph 1 with the `keepWithNext="0"` attribute.

This is paragraph 2.

RML Example 55 : Condpagebreak



An example with `keepWithNext="1"`. There is a spacer underneath

This is paragraph 1, whose style has the `keepWithNext="1"` attribute.
This is paragraph 2.

condPageBreak

The `<condPageBreak/>` tag will move to the next page if there is not enough space on the page. The length required to stay on the same page is give by the attribute `height` which takes a length in the allowed measurements.

Blah blah blah blah blah Lieutenant
Commander Data Harry Kim blah blah blah blah
blah blah blah blah blah blah blah blah.
Blah cloaking device blah blah Lieutenant
Commander Data blah Dr. Pulaski blah blah
blah USS Enterprise blah blah blah emergency
transponder. Blah blah Ferrengi blah blah blah
blah blah blah blah blah blah blah. Blah
blah blah blah Tom Paris Archer IV blah

RML Example 55 : Condpagebreak



blah Archer IV blah blah Soyuz class science vessel blah Betazoid blah blah blah warship blah blah blah
blah. Blah blah blah Lieutenant Worf blah blah Lieutenant Worf Vulcan blah blah blah. Blah blah blah
blah Tom Paris blah William Riker blah blah blah Klingon blah Admiral Nakamura blah blah blah
blah blah. Blah blah blah blah blah Romulan ale blah blah blah asteroid field blah blah blah
blah blah. Blah blah blah Memory Alpha blah blah blah Captain Picard
blah blah Romulan blah blah blah Admiral Nakamura blah blah. Blah blah blah Starfleet
Academy blah blah USS Intrepid blah blah blah holodeck blah blah blah
blah blah ...with a phaser! blah blah blah Romulan Vulcan blah blah blah. Blah blah quantum flux
blah blah quantum flux Chief O'Brian blah blah blah. Blah Counsellor Troi blah blah
blah blah USS Intrepid blah blah blah Captain Janeway blah asteroid field blah IKV Pagh blah
blah. Blah blah blah Betazoid blah blah blah IKV Pagh blah blah Captain Janeway blah blah IKV
Pagh. Blah photon torpedo blah blah blah photon torpedo blah blah blah
Ferengi blah blah blah. Blah blah blah United Federation of Planets blah blah
Deep Space Nine blah blah blah. Blah blah "Intruder alert!" Romulan blah blah
blah blah. Blah blah shuttlecraft Ferengi Vulcan blah blah Galaxy class vessel
blah blah. Blah turbolift blah scout ship cruiser blah quantum flux blah blah
blah William Riker blah blah. Blah blah battlecruiser blah
blah Dr. Pulaski Pacifica blah blah turbolift. Blah blah Benzite blah
Bajoran blah blah "Borg Invasion imminent!" blah blah blood wine. Blah emergency
transponder blah Starfleet blah blah blah shuttle bay 2 blah
blah. Blah blah distress signal blah spacedock blah Irumodic Syndrome blah
Romulan ale blah blah "All hands abandon ship! This is not a drill!" blah blah.

The conditional page break comes in here and is set for 3 inches.

This is on the next page since there was less than three inches till the end of the page.

Blah blah blah Lieutenant Commander Data Harry Kim blah blah blah
blah. Blah cloaking device blah Lieutenant Commander Data blah Dr. Pulaski blah USS
Enterprise blah emergency transponder. Blah blah Ferengi blah Tom Paris Archer IV
blah Archer IV blah Soyuz class science vessel blah Betazoid blah blah warship
blah. Blah blah Lieutenant Worf blah Lieutenant Worf Vulcan blah. Blah Tom Paris
blah William Riker blah Klingon blah Admiral Nakamura blah. Blah Romulan ale
blah asteroid field blah Memory Alpha blah Captain Picard blah Romulan
blah Admiral Nakamura blah. Blah Starfleet Academy blah USS Intrepid blah
blah holodeck blah. Blah ...with a phaser! blah Romulan Vulcan blah. Blah quantum
flux blah quantum flux Chief O'Brian blah. Blah Counsellor Troi blah USS Intrepid
blah Captain Janeway blah asteroid field blah IKV Pagh blah. Blah Betazoid
blah IKV Pagh blah Captain Janeway blah IKV Pagh. Blah photon torpedo blah
torpedo blah Ferengi blah. Blah United Federation of Planets blah Deep Space Nine
blah. Blah "Intruder alert!" Romulan blah. Blah shuttlecraft Ferengi Vulcan
blah Galaxy class vessel blah. Blah turbolift blah scout ship cruiser blah quantum
flux blah William Riker blah. Blah battlecruiser blah Dr. Pulaski Pacifica
blah turbolift. Blah Benzite blah Bajoran blah "Borg Invasion imminent!" blah
blood wine. Blah emergency transponder blah Starfleet blah shuttle bay 2
blah. Blah distress signal blah spacedock blah Irumodic Syndrome blah Romulan ale
blah "All hands abandon ship! This is not a drill!" blah.

The conditional page break comes in here and is set for 3 inches.

RML Example 55 : Condpagebreak



This is at the bottom of the page since there are more than 3in remaining.

frameBreakBefore and pageBreakBefore

The `frameBreakBefore` and `pageBreakBefore` are both attributes of the `<paraStyle>` tag.

The `frameBreakBefore` attribute causes the new paragraph to go into the next frame, even if there is still space in the current frame. The default value is 0.

The `pageBreakBefore` attribute causes the new paragraph to go into the next page, even if there is still space in the current frame, or if there are other frames remaining on the page. The default value is 0.

This is an example of `frameBreakBefore`. The next paragraph will be in a new frame.

This paragraph is in a new frame, since its style has the attribute `frameBreakBefore="1"`

RML Example 55 : Condpagebreak



This is an example of `pageBreakBefore`. The next paragraph will be on a new page.

RML Example 55 : Condpagebreak



This paragraph is on a new page. It missed out the frame in the lower right corner of the last page, since its style has `pageBreakBefore="1"`

allowWidows

The `allowWidows` attribute, for the `<paraStyle>` tag, allows the paragraph to have a widow, a line of text, separated from the rest of the paragraph, at the end. The default value for `allowWidows` is 1.

This is an example of `allowWidows="1"`
Blah blah blah blah SQL blah blah blah blah
pizza blah blah blah blah TeX blah blah blah
blah blah. Blah Intercal blah blah blah blah
blah TeX OS/2 TFT display blah Linux blah blah
blah blah crash! blah blah Sun Microsystems
blah Logo blah blah. Blah blah blah blah blah
blah blah blah blah blah VB Tcl/Tk Fortran blah
blah blah awk blah blah blah. Blah blah blah
blah blah blah blah blah blah blah blah
PGP TCP/IP blah blah blah. Blah cgi Modula-3
SQL blah blah blah Delphi blah LISP blah BETA
mailing lists blah. Blah blah blah blah pepperoni
pizza blah blah blah blah blah blah blah blah
blah blah blah blah blah blah monitor blah. Blah
blah blah blah blah blah blah blah blah parallel
languages blah blah blah blah blah blah blah
blah BEER! blah blah. Blah blah beer blah blah
OpenGL monitor blah blah blah blah. Blah blah
blah blah blah blah blah blah blah blah blah
"illiterate programming" blah blah C: drive. Blah

blah blah.
This example has a widow (the line above).

RML Example 55 : Condpagebreak



This is an example of `allowWidows="0"`
Blah blah blah SQL blah blah blah
pizza blah blah blah TeX blah blah
blah blah. Blah Intercal blah blah blah
blah TeX OS/2 TFT display blah Linux blah
blah crash! blah blah Sun Microsystems
blah Logo blah blah. Blah blah blah
blah blah VB Tcl/Tk Fortran blah
blah awk blah blah. Blah blah
blah blah blah blah PGP TCP/IP
blah blah. Blah cgi Modula-3
SQL blah blah Delphi blah LISP
blah BETA mailing lists blah. Blah
blah pepperoni pizza blah blah
blah monitor blah. Blah blah
parallel languages blah BEER!
blah. Blah beer blah OpenGL
monitor blah blah. Blah
blah blah blah

"illiterate programming" blah C: drive. Blah
blah.

This example does not have a widow, since another
line has been brought with it.

allowOrphans

The `allowOrphans` attribute allows the
paragraph to have an orphan, a line of text, left
in the original frame, separated from the rest of
the paragraph. The default value is for this
attribute is 0.

RML Example 55 : Condpagebreak



This is an example of `allowOrphans="0"`

There is no orphan below.

Blah blah blah blah SQL blah blah blah blah
pizza blah blah blah blah TeX blah blah blah
blah blah. Blah Intercal blah blah blah blah
blah TeX OS/2 TFT display blah Linux blah blah
blah blah crash! blah blah Sun Microsystems
Logo blah blah. Blah blah blah blah blah
blah blah blah blah VB Tcl/Tk Fortran blah blah
blah awk blah blah blah. Blah blah blah blah
blah blah blah blah blah blah blah PGP
TCP/IP blah blah blah. Blah cgi Modula-3 SQL
blah blah blah Delphi blah LISP blah BETA
mailing lists blah. Blah blah blah blah pepperoni
pizza blah blah blah blah blah blah blah
blah blah blah blah blah blah monitor blah. Blah
blah blah blah blah blah blah blah parallel
languages blah blah blah blah blah blah
blah BEER! blah blah. Blah blah beer blah blah
OpenGL monitor blah blah blah blah. Blah blah
Phys blah blah blah blah blah blah blah
blah "illiterate programming" blah blah C: drive.

This is an example of `allowOrphans="1"`

There is an orphan below.
Blah blah blah blah SQL blah blah blah blah

pizza blah blah blah blah TeX blah blah blah
blah blah. Blah Intercal blah blah blah blah
blah TeX OS/2 TFT display blah Linux blah blah
blah blah crash! blah blah Sun Microsystems
Logo blah blah. Blah blah blah blah blah
blah blah blah blah blah VB Tcl/Tk Fortran blah
blah blah awk blah blah blah. Blah blah blah
blah blah blah blah blah blah blah PGP
TCP/IP blah blah blah. Blah cgi Modula-3
SQL blah blah blah Delphi blah LISP blah BETA
mailing lists blah. Blah blah blah blah pepperoni
pizza blah blah blah blah blah blah blah
blah blah blah blah blah blah monitor blah. Blah
blah blah blah blah blah blah blah parallel
languages blah blah blah blah blah blah
blah BEER! blah blah. Blah blah beer blah blah
OpenGL monitor blah blah blah blah. Blah blah
Phys blah blah blah blah blah blah blah
blah "illiterate programming" blah blah C: drive.

endDots

The `endDots` attribute fills in the rest of the last line of the paragraph with the characters given for the attribute.

This paragraph should have dots following it until the end of the line.....

This paragraph should have the characters "123" following it until the end of the line. 123123123123123123123123123